

**Rekomendowane odległości punktów przesuwnych.**

**DLA RUR PVC-U PN16**

Ø	ODLEGŁOŚĆ MIĘDZY PODPORAMI [cm]				
	W POZIOMIE				W PIONIE
	PVC-U PN16		PE (SDR 11)		PVC-U PN16 MIĘDZY 20°C a 40°C
	20°C	40°C	20°C	40°C	
20	85	50	30	26	90
25	90	55	40	34	100
32	100	65	50	42	120
40	110	80	60	51	140
50	125	95	70	60	160
63	140	110	90	77	180
75	150	120	100	85	200
90	165	135	120	102	220
110	185	155	150	128	240
125	200	170	160	136	250
140	215	185	180	153	250
160	225	200	200	170	250
200	250	225	240	204	250
225	250	225	260	221	250
250	250	225	280	238	250

**DLA RUR PVC-C PN10**

Ø	20°C	30°C	40°C	50°C	60°C	70°C	80°C
	[mm]	[mm]	[mm]	[mm]	[mm]	[mm]	[mm]
16	1000	950	900	850	750	675	600
20	1150	1100	1025	950	875	775	700
25	1200	1150	1100	1000	900	800	700
32	1350	1250	1200	1100	1000	900	800
40	1500	1400	1300	1250	1150	1050	900
50	1650	1600	1500	1400	1300	1200	1100
63	1850	1750	1650	1600	1500	1350	1250
75	2050	1950	1850	1750	1650	1500	1350
90	2250	2100	2000	1900	1800	1650	1500
110	2500	2350	2200	2100	1950	1800	1650
125	2650	2500	2350	2250	2100	1950	1750
140	2800	2650	2500	2350	2200	2050	1850
160	3000	2850	2700	2550	2400	2200	2000
180	3150	3000	2850	2700	2500	2300	2100
200	3350	3150	3000	2850	2650	2450	2200
225	3550	3350	3200	3000	2800	2600	2350
250	3750	3550	3350	3150	3000	2750	2500
280	3950	3750	3550	3350	3250	2900	2650
315	4200	4000	3750	3550	3350	3050	2800
355	4450	4250	4000	3800	3550	3250	2950
400	4750	4500	4250	4000	3750	3450	3150